



GRUPO MAMSA

ALQUILER Y VENTA DE MAQUINARIA

- Desde 1979 -

FICHA TÉCNICA

Maquinaria profesional
Sostenible · Respetuosa · Eficaz

900 460 060

www.grupomamsa.com

TORO®

HD PROLINE

WALK POWER MOWERS





SPECIFICATIONS

MODEL	22291	22280
ENGINE*	Kawasaki®, 4-cycle, 179 cc, FJ180V	Kawasaki, 4-cycle, 179 cc, FJ180V
STARTER	Recoil, Zone Start	▶ Recoil, Blade Brake Clutch
TYRES	23 cm x 5 cm Rubber Tyres	22.86 cm x 5.08 cm Rubber Tyres
FUEL CAPACITY	Petrol / 1.9 litres	▶ Petrol / 3.8 litres
TRANSMISSION / DRIVE SYSTEM	Self Propel / Fixed Speed, Rear Wheel Drive	▶ Self Propel / 3-Speed, RWD
SPEED	0-6.0 km/h forward	0-6.0 km/h forward
WEIGHT	50 kg	56 kg
DECK WIDTH	53 cm	53 cm
DECK TYPE	Recycler/Rear Bag, Aluminum	Recycler/Rear Bag, Aluminum
HEIGHT OF CUT	25 mm – 114 mm, 4 point	25 mm – 114 mm, 4 point
BLADE	3.4 mm steel w/ blade stiffener	3.4 mm steel w/ blade stiffener
CONTROL SYSTEM	Two-Bail	Two-Bail
STEEL DECK WEAR PLATES	Optional with Deck Side Guard Kit (130-9701)	Standard
ENGINE GUARD	Optional with Engine Guard Kit (130-9700)	Standard

▶ = Enhanced or step-up feature



COMMERCIAL GRADE WHEELS

Tough co-polymer wheels feature precision ball bearings for long life, less downtime and lower replacement costs. These large 23 cm x 5 cm wheels also provide a light footprint that is easy on turf.



EASY EMPTY BAG

The 74 litre bag features an easy-empty design, making quick work of clipping disposal.



REAR BAGGING SYSTEM

The wide opening and ramped profile of the tunnel maximize bag fill.



STEEL DECK WEAR PLATE

Extend the life of your mower deck with replaceable steel wear plates that protect against bottom and side impacts. Select models.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your dealer for details on all our warranties.

toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258

©2018 The Toro Company.
All Rights Reserved.
GB 200-8003NA



facebook.com/ToroCompany
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope



Count on it.